

# K-BKR KOM

Ball valves (wafer type), with double-acting actuator

**HANSA FLEX**

## 属性

|        |   |
|--------|---|
| 结构类型   | Pneumatic actuators, in double- or single acting version, with integrated end-position feedback |
| 工作压力   | DN 15 - DN 50: max. 40 bar; DN 65 - DN 100: max. 16 bar   |
| 工作温度   | -20 °C to +70 °C  |
| 旋转角    | 90 °  |
| 控制压力   | 5.5 bar   |
| 阀门适配器  | Acc. to NAMUR   |
| 驱动器    | aluminium eloxed  |
| 驱动器密封件 | NBR   |
| 球阀     | Stainless steel 1.4408, with ISO-flange plate   |
| 球阀密封件  | PTFE  |



## 提示

其它数据应客户要求提供。

## 描述

2-way ball valves compact flange type, full bore

## 货品

| 名称             | DN  | A<br>(mm) | B<br>(mm) | C<br>(mm) | D<br>(mm) | E<br>(mm) | F<br>(mm) |
|----------------|-----|-----------|-----------|-----------|-----------|-----------|-----------|
| K- 07 30 02 76 | 15  | 116,0     | 125,0     | 40,0      | 95,0      | 45,0      | 61,5      |
| K- 07 30 02 77 | 20  | 116,0     | 129,3     | 44,0      | 105,0     | 58,0      | 61,5      |
| K- 07 30 02 78 | 25  | 133,0     | 138,6     | 53,0      | 115,0     | 68,0      | 68,5      |
| K- 07 30 02 79 | 32  | 137,0     | 158,2     | 58,4      | 135,0     | 78,0      | 80,0      |
| K- 07 30 02 80 | 40  | 161,0     | 176,3     | 62,0      | 145,0     | 88,0      | 92,5      |
| K- 07 30 02 81 | 50  | 161,0     | 185,5     | 78,0      | 155,0     | 102,0     | 92,5      |
| K- 07 30 02 82 | 65  | 180,0     | 205,0     | 100,0     | 185,0     | 122,0     | 92,5      |
| K- 07 30 02 83 | 80  | 209,0     | 240,0     | 120,0     | 200,0     | 138,0     | 110,5     |
| K- 07 30 02 75 | 100 | 221,0     | 272,0     | 152,0     | 220,0     | 158,0     | 120,0     |