


K-RD VOLLER DURCHGANG

Non-return valves

HANSA FLEX

属性

| | |
|------|-----------------------|
| 工作温度 | -10 °C to +100 °C |
| 开口压力 | 20 mbar |
| 密封材料 | NBR |
| 弹簧 | Stainless-steel |
| 壳体 | Brass |
| 滑座 | Polyether imide (PEI) |



提示

其它数据应客户要求提供。

描述

Economy non-return valves with full passage and very low opening pressure.

货品

| 名称 | 螺纹 | 长度 (mm) | 最大工作压力 (bar) | SW (mm) |
|----------------|----------|------------|-----------------|------------|
| K- 07 30 24 53 | Rp 3/8 | 47,0 | 40 | 20 |
| K- 07 30 24 54 | Rp 1/2 | 59,0 | 40 | 25 |
| K- 07 30 24 55 | Rp 3/4 | 65,0 | 40 | 31 |
| K- 07 30 24 56 | Rp 1 | 75,0 | 25 | 38 |
| K- 07 30 24 57 | Rp 1 1/4 | 83,0 | 25 | 48 |
| K- 07 30 24 58 | Rp 1 1/2 | 89,0 | 16 | 54 |
| K- 07 30 24 59 | Rp 2 | 101,0 | 16 | 67 |