

# K-SPV EINFACH

Check valves, single-acting - spring to close

**HANSA FLEX**

## 属性

工作压力	最大 10 巴
控制压力	min. 3.0 bar, max. 8 bar with double-acting actuator; min. 4.2 bar, max. 8 bar for single-drive
温度	-20 °C to +80 °C (NBR); -20 °C to +150 °C (FKM)
接口	NAMUR-Interface, direct: 2 x G 1/8
装入位置	Any
壳体,内部部件	Nickel-plated brass
弹簧	Stainless-steel
密封材料	Perbunan (NBR) or FKM (FPM)



## 提示

其它数据应客户要求提供。

## 描述

2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. <br>These valves have a full bore.

## 货品

名称	DN	螺纹	密封材料	H (mm)	L (mm)
K- 07 30 25 45	10	Rp 3/8	NBR	46,0	98,0
K- 07 30 25 46	15	Rp 1/2	NBR	51,7	112,0
K- 07 30 25 47	20	Rp 3/4	NBR	63,5	135,0
K- 07 30 25 48	25	Rp 1	NBR	69,0	143,0
K- 07 30 25 49	10	Rp 3/8	FKM	46,0	98,0
K- 07 30 25 50	15	Rp 1/2	FKM	51,7	112,0
K- 07 30 25 51	20	Rp 3/4	FKM	63,5	135,0
K- 07 30 25 52	25	Rp 1	FKM	69,0	143,0