


K-HOCHLEIST SCHALLDAEMP

High-performance silencers

HANSA FLEX

属性

| | |
|--------|--|
| 工作温度 | -10 °C to +90 °C |
| 装入位置 | Any |
| 动压(入口) | Max. 6 bar |
| 原料 | Steel housing powder coated, perforated sheet galvanized steel, polyester felt discs |



提示

其它数据应客户要求提供。

描述

Multi-chamber silencers with a high blow-off rate, short exhaust time and excellent silencing effect.

货品

| 名称 | 流量 6 bar | 螺纹 | A (mm) | B (mm) | C (mm) |
|----------------|-------------|---------|-----------|-----------|-----------|
| K- 07 40 14 31 | 13350 l/min | G 1/2 | 14,0 | 103,0 | 80,0 |
| K- 07 40 14 32 | 16700 l/min | G 3/4 | 16,0 | 106,0 | 80,0 |
| K- 07 40 14 33 | 23350 l/min | G 1 | 18,0 | 130,0 | 110,0 |
| K- 07 40 14 34 | 31700 l/min | G 1 1/4 | 20,0 | 136,0 | 110,0 |
| K- 07 40 14 35 | 53400 l/min | G 1 1/2 | 24,0 | 168,0 | 150,0 |
| K- 07 40 14 36 | 56700 l/min | G 2 | 24,0 | 168,0 | 150,0 |