


# K-INLINE-DRG AG IG M SEKUNDAERENTLU

Inline pressure regulators, female/male thread, self-relieving



| 属性   |  |
|------|--|
| 工作压力 | Max. 25 bar                            |
| 温度范围 | 0 °C to +80 °C                         |
| 壳体   | Aluminium                              |
| 其余部件 | Stainless steel, nitrile rubber, brass |



**提示**  
其它数据应客户要求提供。

**描述**  
The majority of pneumatic tools are connected directly to the compressed air supply by means of a quick disconnect coupling, in other words they tend to be supplied with a higher pressure than is actually required. Which increases consumption and leads to tool overload. Added safety is provided by the automatic self-relieving function. If the tool is disconnected from the hose, it continues to work for a short period, even though it has been switched off, owing to the residual pressure that is present on the tool side.   
Inadvertent operation of the tool can thus lead to serious injuries to the user (tackers or nail drivers can fire up to another ten shots).   
This effect can be prevented by using the inline pressure regulators, which have a preset pressure determined by the application, thereby achieving energy efficiency and economy.

| 货品             |       |         |                 |           |            |
|----------------|-------|---------|-----------------|-----------|------------|
| 名称             | 螺纹    | 工作压力已预设 | 流量              | A<br>(mm) | SW<br>(mm) |
| K- 07 25 02 97 | G 1/4 | 2 bar   | 600 - 800 l/min | 66,6      | 16         |
| K- 07 25 02 98 | G 1/4 | 3 bar   | 600 - 800 l/min | 66,6      | 16         |
| K- 07 25 02 99 | G 1/4 | 4 bar   | 600 - 800 l/min | 66,6      | 16         |
| K- 07 25 03 00 | G 1/4 | 5 bar   | 600 - 800 l/min | 66,6      | 16         |
| K- 07 25 03 01 | G 1/4 | 6 bar   | 600 - 800 l/min | 66,6      | 16         |
| K- 07 25 03 02 | G 1/4 | 8 bar   | 600 - 800 l/min | 66,6      | 16         |