

K-KM MS

Hexagonal lock nuts, brass

属性

| | |
|------|-------------|
| 工作压力 | 10 bar |
| 介质温度 | max. +90 °C |
| 环境温度 | Max. +90 °C |



提示

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. 其它数据应客户要求提供。

附加信息

Further types and dimensions on request.

货品

| 名称 | 螺纹 | L1 (mm) | SW |
|----------------|------------|------------|-------|
| K- 07 40 34 45 | G 1/8 | 3,5 | 15 mm |
| K- 07 40 34 46 | G 1/4 | 3,5 | 17 mm |
| K- 07 40 34 47 | G 3/8 | 4,5 | 19 mm |
| K- 07 40 34 48 | G 1/2 | 5,0 | 24 mm |
| K- 07 40 34 49 | G 3/4 | 5,0 | 32 mm |
| K- 07 40 34 50 | G 1 | 6,0 | 41 mm |
| K- 07 40 44 33 | G 1 1/4 | 8,5 | 50 mm |
| K- 07 40 44 34 | G 1 1/2 | 8,5 | 60 mm |
| K- 07 40 44 35 | G 2 | 11,0 | 70 mm |
| K- 07 40 34 51 | M 10 x 1 | 4,0 | 14 mm |
| K- 07 40 34 52 | M 12 x 1 | 5,0 | 17 mm |
| K- 07 40 34 54 | M 14 x 1 | 4,0 | 19 mm |
| K- 07 40 34 55 | M 16 x 1 | 5,0 | 22 mm |
| K- 07 40 34 56 | M 20 x 1.5 | 4,5 | 27 mm |
| K- 07 40 34 57 | M 22 x 1 | 4,5 | 27 mm |
| K- 07 40 34 58 | M 28 x 1,5 | 6,0 | 36 mm |