K-OEL WS TRENNER DRUKOSEP

»drukosep« oil-water separators

属性

容器	Polyethylene / Polypropylene
过滤器	Polypropylene / activated carbon



提示

其它数据应客户要求提供。

描述

For compressor capacities up to 3.5 m3/min. Why treat condensate? Condensate is produced whenever air is compressed. The amount of condensate depends on the size and operating time of the compressor. The condensate produced by oil-lubricated compressors can contain up to 2000 mg of oil per litre! According to § 7a of the Water Resources Policy Act, this condensate must be treated in line with the latest state of the art before it can be introduced into the public sewer system.
The maximum limit is 20 mg of oil per litre of water. If the condensate is not treated, it must be collected and disposed of by a specialist firm upon proof. »drukosep« separates the oil from the condensate with a combination of coalescence and activated carbon filters. The cleaned water can be discharged into the public sewer system, while the waste oil collects in the combination filter and can be disposed of together with it. Benefits of »drukosep«: Compact design, Secure wall or floor mounting, 3-stage combination filter, Test glass for the cleaned condensate.

货品

名称	最大压缩机功率 (m3/min)	高度 (mm)	宽度 (mm)	深度 (mm)	重量 (kg)
K- 07 25 09 25	1,5	445	251,0	240,0	4,3
K- 07 25 09 26	2,5	545	251,0	240,0	5,5
K- 07 25 09 27	3,5	613	373,0	291,0	9,0

附件

K-ZUBEH DRUKOSEP	Accessories for oil-water separators

备件

K-ERSATZFILTERSET DRUOSEP	Replacement filter set for oil-water separators

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。