
K-PROP REGELVE SENTRONIC D

Proportional control valves, digital, 24 VDC

HANSA/FLEX

属性					
介质温度	0 - 60 °C				
环境温度	0 - 50 °C				
适用介质	Air or neutral gases (≤ 50 µm filter specified)				
压力范围	0 - 10 bar				
触发	0 to 10 V (on request: 0 to 20 mA or 4 to 20 mA)				
电子额定值	0 - 10 V				
模拟输出端	0 - 10 V				
操纵件	Proportional solenoid valve				
数字输出端	Pressure switch output PNP +/- 5%				
Failsafe 位置	Pressure relieved in case of loss of voltage				
内部部件	РОМ				
密封材料	NBR				
売体	Aluminium				



提示

其它数据应客户要求提供。

描述

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital.

<

货品					
名称	接口	DN	流量	В	С
			(L/min)		(mm)
K- 07 25 10 04	G 1/8	4	780	52,0 mm	112,0
K- 07 25 10 05	G 1/4	4	780	52,0 mm	112,0
K- 07 25 10 06	G 1/4	8	1750	66,0 mm	138,0
K- 07 25 10 07	G 3/8	8	1750	66,0 mm	138,0