

K-HOCHLEIST DRUCKREGLER

Heavy-duty pressure regulators

HANSA FLEX

属性

| | |
|-------|--|
| 入口压力 | Max. 25 bar |
| 介质温度 | max. 60 °C |
| 环境温度 | Max. 60 °C |
| 流量 | 50000 l/min |
| 密封材料 | NBR |
| 壳体 | Aluminium, painted silver |
| 流量值测量 | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



提示

其它数据应客户要求提供。

描述

Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design for very high flow rates. Separate indication of input and working pressure on two pressure gauges. The pressure setting can be locked by pushing the knob down. We recommend always using these controllers in conjunction with our K-07250607 and K-07250609 filters.

货品

| 名称 | 螺纹 | 调节范围 | A (mm) | B | DN |
|----------------|---------|--------------|-----------|----------|----|
| K- 07 25 08 03 | G 1 1/2 | 0.1 - 3 bar | 188,0 | 261,0 mm | 50 |
| K- 07 25 08 04 | G 1 1/2 | 0.2 - 6 bar | 188,0 | 261,0 mm | 50 |
| K- 07 25 08 05 | G 1 1/2 | 0.5 - 10 bar | 188,0 | 261,0 mm | 50 |
| K- 07 25 08 06 | G 1 1/2 | 0.5 - 16 bar | 188,0 | 261,0 mm | 50 |
| K- 07 25 08 07 | G 2 | 0.1 - 3 bar | 160,0 | 261,0 mm | 50 |
| K- 07 25 08 08 | G 2 | 0.2 - 6 bar | 160,0 | 261,0 mm | 50 |
| K- 07 25 08 09 | G 2 | 0.5 - 10 bar | 160,0 | 261,0 mm | 50 |
| K- 07 25 08 10 | G 2 | 0.5 - 16 bar | 160,0 | 261,0 mm | 50 |

备件

| | |
|----------------------------|----------------------|
| K-VERSCHLEI-SATZ | Set of wearing parts |
| K-LOESBARE DOPPELNIPPEL MS | Double nipples |