


属性

入口压力	2.5 - 16 bar
温度范围	-10 °C to +50 °C
适用介质	压缩空气
接口螺纹	Material: Die-cast zinc
壳体	Material: Grivory® (PA 66)
流量值测量	At P2 = 6 bar, pressure drop $\Delta p = 1$ bar



提示

其它数据应客户要求提供。

描述

Seat valves operated by secondary pressure for controlled pressurisation of pneumatic systems. These valves prevent a sudden build-up of pressure accompanied by dangerous, jerky cylinder movements. The full cross-section of the regulator is opened at 50% of the input pressure. The filling time can be altered by turning the adjusting screw.

附加信息

See 3/2-way valves and filling units

See 3/2-way valves and filling units

货品

名称	螺纹	流量 (L/min)	A (mm)	B	C (mm)	D (mm)
K-07 25 11 11	G 1/4	1300	52,0	78,0 mm	45,0	33,0
K-07 25 11 12	G 3/8	1300	52,0	78,0 mm	45,0	33,0
K-07 25 11 13	G 3/8	3400	63,0	111,5 mm	53,5	58,0
K-07 25 11 14	G 1/2	3400	63,0	111,5 mm	53,5	58,0
K-07 25 11 15	G 3/4	8750	85,0	112,0 mm	58,0	54,0
K-07 25 11 16	G 1	8750	85,0	112,0 mm	58,0	54,0

备件

K-HALTERBAUSATZ HANSA Holder HANSA