


K-NEBELOELER PC-BEHAEL S MULTIFIX

Oil-mist lubricators with polycarbonate bowl and bowl guard

HANSA FLEX

属性

| | |
|-------------|--|
| 入口压力 | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| 介质温度 | max. 60 °C |
| 环境温度 | Max. 60 °C |
| 密封材料 | NBR |
| 壳体 | Die-cast zinc, Aluminium for G 1 variant |
| 泄水头 | PA (polycarbonate bowl), Zinc-glass-NBR (metal bowl) |
| Drain valve | Manual |
| 油种类 | CL 32 acc. to DIN 51517 - ISO VG 32 |
| 流量值测量 | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



提示

其它数据应客户要求提供。

描述

Proportional lubricators, oil can be filled under pressure.

货品

| 名称 | 螺纹 | 流量 (L/min) | A (mm) | B | C (mm) | D (mm) | DN | 结构尺寸 |
|----------------|-------|---------------|-----------|----------|-----------|-----------|----|------|
| K- 07 25 00 93 | G 1/4 | 1900 | 47,8 | 167,8 mm | 58,0 | 109,8 | 6 | 1 |
| K- 07 25 00 96 | G 3/8 | 1900 | 47,8 | 167,8 mm | 58,0 | 109,8 | 10 | 1 |
| K- 07 25 00 99 | G 1/2 | 5000 | 68,8 | 198,6 mm | 66,1 | 132,5 | 15 | 2 |
| K- 07 25 01 02 | G 3/4 | 5000 | 68,8 | 198,6 mm | 66,1 | 132,5 | 20 | 2 |
| K- 07 25 01 05 | G 1 | 18000 | 100,0 | 324,3 mm | 82,7 | 241,6 | 25 | 3 |

备件

| | |
|----------------------------------|-------------------------------|
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-METALLBEHAELTER OELER MULTIFIX | Metal tank oiler |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-SCHUTZKORB G | Protective cage |
| K-TROPFAUFSATZ POLYCARBO 1 | Drip attachment polycarbonate |
| K-TROPFAUFSATZ METALL | Drip attachment metal |