

K-PRAEZI DRUCKREGLER MULTIFIX

Precision pressure regulators

HANSA FLEX

属性

| | |
|--------|--|
| 入口压力 | Max. 16 bar |
| 介质温度 | max. 60 °C |
| 环境温度 | Max. 60 °C |
| 密封材料 | NBR |
| 弹簧罩 | POM-brass |
| 壳体 | Die-cast zinc |
| 自身空气消耗 | 2.6 l/min, depending on secondary pressure |
| 流量值测量 | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



提示

其它数据应客户要求提供。

描述

Diaphragm pressure regulators, independent of inlet pressure, with self-relieving design and very high flow rate. The pressure setting can be locked by pushing the button down.

订购指南

Lockable precision pressure regulators available on request

货品

| 名称 | 螺纹 | 调节范围 | 流量 (L/min) | A (mm) | B | C (mm) | D (mm) | DN | 结构尺寸 |
|----------------|-------|--------------|---------------|-----------|----------|-----------|-----------|----|------|
| K- 07 25 00 37 | G 1/4 | 0.1 - 3 bar | 1500 | 47,8 | 94,8 mm | 67,0 | 27,8 | 6 | 1 |
| K- 07 25 00 38 | G 1/4 | 0.2 - 6 bar | 1500 | 47,8 | 94,8 mm | 67,0 | 27,8 | 6 | 1 |
| K- 07 25 00 36 | G 1/4 | 0.5 - 10 bar | 1500 | 47,8 | 94,8 mm | 67,0 | 27,8 | 6 | 1 |
| K- 07 25 00 40 | G 1/2 | 0.1 - 3 bar | 6000 | 68,8 | 134,1 mm | 99,0 | 35,1 | 15 | 2 |
| K- 07 25 00 41 | G 1/2 | 0.2 - 6 bar | 6000 | 68,8 | 134,1 mm | 99,0 | 35,1 | 15 | 2 |
| K- 07 25 00 39 | G 1/2 | 0.5 - 10 bar | 6000 | 68,8 | 134,1 mm | 99,0 | 35,1 | 15 | 2 |

备件

| | |
|--------------------------|----------------------|
| K-HALTERBAUSATZ | Holder |
| K-SCHALTTAFELMUTTER | Nut |
| K-HALTERBAUSATZ MULTIFIX | Holder |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |
| K-VERSCHLEI-SATZ | Set of wearing parts |