

K-VT BREIT MULTIFIX

Manifolds - wide design

HANSA FLEX

属性

| | |
|-------|--|
| 入口压力 | Max. 16 bar |
| 介质温度 | max. 60 °C |
| 环境温度 | Max. 60 °C |
| 密封材料 | NBR |
| 壳体 | Die-cast zinc |
| 流量值测量 | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



提示

Flow rate l/min at P → A
其它数据应客户要求提供。

描述

Wide or narrow, four-way manifolds.

货品

| 名称 | Outlets | 螺纹 | 流量 (L/min) | A (mm) | B | C (mm) | 结构尺寸 |
|----------------|------------------|-------|---------------|-----------|---------|-----------|------|
| K- 07 25 11 73 | 4 x 1/4 | G 1/4 | 2500 | 47,8 | 52,0 mm | 26,0 | 1 |
| K- 07 25 11 74 | 4 x 1/4 | G 3/8 | 2500 | 47,8 | 52,0 mm | 26,0 | 1 |
| K- 07 25 11 75 | 2 x 1/4, 2 x 1/2 | G 1/2 | 11000 | 68,8 | 67,0 mm | 33,5 | 2 |
| K- 07 25 11 76 | 2 x 1/4, 2 x 1/2 | G 3/4 | 11000 | 68,8 | 67,0 mm | 33,5 | 2 |

附件

| | |
|-------------------------------------|---|
| K-DRS WECHSELKONTAK ANFLANSCHBAR DS | Pressure switches, changeover type, suitable for flange mounting K-07302861 |
| K-ZUBEH HANSA | Accessories for pressure switch HANSA |

备件

| | |
|---------------------|-----------------|
| K-KOPPELPAKET MEHR | Coupling packet |
| K-KOPPELPAKET SCHMA | Coupling packet |