

K-FI METALLBEHAEL H ALV MULTIFIX MI

Filters with metal bowl and semi-automatic drain valve

HANSA FLEX

属性

| | |
|-------------|--|
| 入口压力 | Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl) |
| 介质温度 | max. 60 °C |
| 环境温度 | Max. 60 °C |
| 流量 | 1000 l/min |
| 过滤器元件中的气孔宽度 | 5 µm |
| 壳体 | Die-cast zinc |
| Drain valve | Semi-automatic |
| 流量值测量 | At P2 = 6 bar and pressure drop $\Delta p = 1$ bar |



提示

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. 其它数据应客户要求提供。

描述

Centrifugal separators with a sintered filter element.

货品

| 名称 | 螺纹 | A (mm) | B | C (mm) | D (mm) | DN | 结构尺寸 |
|----------------|-------|-----------|----------|-----------|-----------|----|------|
| K- 07 25 00 43 | G 1/8 | 40,0 | 111,6 mm | 12,3 | 99,3 | 5 | 0 |
| K- 07 25 00 45 | G 1/4 | 40,0 | 111,6 mm | 12,3 | 99,3 | 5 | 0 |

备件

| | |
|--------------------------------|--|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-ERSATZBEHAELTER MULTI MINI | Spare tank »multifix-mini« & »standard-mini« |
| K-PC-BEHAELTER FILTER MULTIFIX | Polycarbonate tank filter |
| K-FILTERELEMENT | Filter element |