

# K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

**HANSA FLEX**

## 属性

入口压力	Min. 2 bar, max. 10 bar
介质温度	max. 60 °C
环境温度	Max. 60 °C
电接口	Device plug PG 9, type B, EN 175301-803
保护等级	IP 65 (P 54) acc. to DIN 40050
流量	1600 l/min
相对接通持续时间	100 %
排气接口	Silencer G 1/4
密封材料	NBR
壳体	Die-cast zinc
流量值测量	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



## 提示

If several devices in the »multiflex-mini« Series are assembled together, the maximum working pressure is 12 bar. 其它数据应客户要求提供。

## 描述

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

## 货品

名称	螺纹	电磁线圈	A (mm)	B	C (mm)	结构尺寸
K- 07 25 11 62	G 1/4	230 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 63	G 1/4	110 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 64	G 1/4	24 V DC	45,0	29,0 mm	96,0	0

## 备件

K-KOPPELPAKET MEHR	Coupling packet
K-GERAETESTECKER	Coupling socket
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-MAGNETSPULE MULTIFIX	Solenoid
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted