
# K-WTEH 2-TLG PC-BEHAEL VARIOBLOC

Service units, 2-piece with polycarbonate bowl



属性			
入口压力	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)		
介质温度	max. 50 °C		
环境温度	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)		
过滤器元件中的气孔宽度	40 μm		
密封材料	NBR		
弹簧罩	POM		
売体	Die-cast zinc		
膜片	NBR		
泄水头	PA		
Drain valve	Manual		
流量值测量	At P1 = 10 bar, P2 = 6 bar and pressure drop Δp = 1 bar		





# 提示

其它数据应客户要求提供。

#### 描述

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

# 订购指南

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges (0.5 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

# 附加信息

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges.

### 货品

名称	螺纹	调节范围	流量	Α	В	С
			(L/min)	(mm)		(mm)
K- 07 25 13 85	G 1/4	0.5 - 10 bar	1500	96,0	203,0 mm	68,0
K- 07 25 13 87	G 3/8	0.5 - 10 bar	1800	96,0	203,0 mm	68,0
K- 07 25 13 89	G 1/2	0.5 - 10 bar	3400	140,0	273,0 mm	98,0
K- 07 25 13 91	G 3/4	0.5 - 10 bar	5000	140,0	273,0 mm	98,0
K- 07 25 13 93	G 1	0.5 - 10 bar	5000	194,0	273,0 mm	98,0

备件			
K-VERSCHLEI-SATZ VARIOBLOC	Set of wearing parts		
K-FILTERELEMENT VARIOBLOC	Filter element		
K-TROPFAUFSATZ VARIOBLOC	Drip attachment		
K-ERSATZBEHAELTER VARIOBLOC POLY	Spare tank Polycarbonat		
K-ABLASSVENTIL AUTO	Fully-automatic drain valve with Adapter G 1/8		
K-TROPFAUFSATZ METALL	Drip attachment metal		