

K-DRV ABLD SCHNVERSCHR C RAENDEL

Unidirectional flow control valves, outgoing air restriction (»C«), quick-lock screw fitting

HANSA FLEX

属性

| | |
|----------------|------------------------------------|
| 工作压力 | 最大 10 巴 |
| 温度范围 | 0 °C to +70 °C |
| 空心螺钉, 摆臂, 调节螺钉 | Nickel-plated brass |
| 内部部件 | Brass with a bare metal surface |
| O 形圈凸缘密封件 | NBR |
| 密封(防丢失) | Polyamide (glass fibre-reinforced) |



提示

其它数据应客户要求提供。

描述

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

货品

| 名称 | C (mm) | 用于软管 | 螺纹 | SW | B (mm) |
|----------------|-----------|---------------|-------|-------|-----------|
| K- 07 15 04 54 | 18,0 | 4 mm / 2,5 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 04 55 | 19,0 | 5 mm / 3 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 04 56 | 19,0 | 6 mm / 4 mm | M 5 | 8 mm | 38,9 |
| K- 07 15 04 63 | 25,0 | 6 mm / 4 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 04 64 | 25,0 | 8 mm / 6 mm | G 1/8 | 14 mm | 42,4 |
| K- 07 15 04 60 | 26,5 | 6 mm / 4 mm | G 1/4 | 17 mm | 51,4 |
| K- 07 15 04 61 | 27,5 | 8 mm / 6 mm | G 1/4 | 17 mm | 51,4 |
| K- 07 15 04 59 | 28,5 | 10 mm / 8 mm | G 1/4 | 17 mm | 51,4 |