

# K-DRV ABLD SCHNVERSCHR C RAENDEL

Unidirectional flow control valves, outgoing air restriction (»C«), quick-lock screw fitting

**HANSA FLEX**

## 属性

|                |                                    |
|----------------|------------------------------------|
| 工作压力           | 最大 10 巴                            |
| 温度范围           | 0 °C to +70 °C                     |
| 空心螺钉, 摆臂, 调节螺钉 | Nickel-plated brass                |
| 内部部件           | Brass with a bare metal surface    |
| O 形圈凸缘密封件      | NBR                                |
| 密封(防丢失)        | Polyamide (glass fibre-reinforced) |



## 提示

其它数据应客户要求提供。

## 描述

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## 货品

| 名称             | C<br>(mm) | 用于软管          | 螺纹    | SW    | B<br>(mm) |
|----------------|-----------|---------------|-------|-------|-----------|
| K- 07 15 04 54 | 18,0      | 4 mm / 2,5 mm | M 5   | 8 mm  | 38,9      |
| K- 07 15 04 55 | 19,0      | 5 mm / 3 mm   | M 5   | 8 mm  | 38,9      |
| K- 07 15 04 56 | 19,0      | 6 mm / 4 mm   | M 5   | 8 mm  | 38,9      |
| K- 07 15 04 63 | 25,0      | 6 mm / 4 mm   | G 1/8 | 14 mm | 42,4      |
| K- 07 15 04 64 | 25,0      | 8 mm / 6 mm   | G 1/8 | 14 mm | 42,4      |
| K- 07 15 04 60 | 26,5      | 6 mm / 4 mm   | G 1/4 | 17 mm | 51,4      |
| K- 07 15 04 61 | 27,5      | 8 mm / 6 mm   | G 1/4 | 17 mm | 51,4      |
| K- 07 15 04 59 | 28,5      | 10 mm / 8 mm  | G 1/4 | 17 mm | 51,4      |