
K-DV SCHNVERSCHR B RAENDEL

Bidirectional flow control valves, air restriction at both ends (»B«), quick-lock screw fitting



属性	
工作压力	最大 10 巴
温度范围	0 °C to +70 °C
空心螺钉,摆臂,调节螺钉	Nickel-plated brass
内部部件	Brass with a bare metal surface
O 形圖凸缘密封件	NBR
密封(防丢失)	Polyamide (glass fibre-reinforced)





提示

其它数据应客户要求提供。

描述

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly.
br>On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

货品					
C (mm)	用于软管	螺纹	SW	B (mm)	
18,0	4 mm / 2,5 mm	M 5	8 mm	38,9	
19,0	5 mm / 3 mm	M 5	8 mm	38,9	
19,0	6 mm / 4 mm	M 5	8 mm	38,9	
23,0	5 mm / 3 mm	G 1/8	14 mm	42,0	
25,0	6 mm / 4 mm	G 1/8	14 mm	42,0	
25,0	8 mm / 6 mm	G 1/8	14 mm	42,0	
26,5	6 mm / 4 mm	G 1/4	17 mm	51,0	
27,5	8 mm / 6 mm	G 1/4	17 mm	51,0	
28,5	10 mm / 8 mm	G 1/4	17 mm	51,0	
	(mm) 18,0 19,0 19,0 23,0 25,0 25,0 26,5 27,5	(mm) 18,0	(mm) 18,0 4 mm / 2,5 mm M 5 19,0 5 mm / 3 mm M 5 19,0 6 mm / 4 mm M 5 23,0 5 mm / 3 mm G 1/8 25,0 6 mm / 4 mm G 1/8 25,0 8 mm / 6 mm G 1/8 26,5 6 mm / 4 mm G 1/4 27,5 8 mm / 6 mm G 1/4	(mm) 18,0 4 mm / 2,5 mm M 5 8 mm 19,0 5 mm / 3 mm M 5 8 mm 19,0 6 mm / 4 mm M 5 8 mm 23,0 5 mm / 3 mm G 1/8 14 mm 25,0 6 mm / 4 mm G 1/8 14 mm 25,0 8 mm / 6 mm G 1/8 14 mm 26,5 6 mm / 4 mm G 1/4 17 mm 27,5 8 mm / 6 mm G 1/4 17 mm	