


# K-DV SCHNVERSCHR B RAENDEL

Bidirectional flow control valves, air restriction at both ends (»B«), quick-lock screw fitting

**HANSA FLEX**

## 属性

工作压力	最大 10 巴
温度范围	0 °C to +70 °C
空心螺钉,摆臂,调节螺钉	Nickel-plated brass
内部部件	Brass with a bare metal surface
O 形圈凸缘密封件	NBR
密封(防丢失)	Polyamide (glass fibre-reinforced)



## 提示

其它数据应客户要求提供。

## 描述

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. <br>On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## 货品

名称	C (mm)	用于软管	螺纹	SW	B (mm)
K-07 15 04 90	18,0	4 mm / 2,5 mm	M 5	8 mm	38,9
K-07 15 04 91	19,0	5 mm / 3 mm	M 5	8 mm	38,9
K-07 15 04 92	19,0	6 mm / 4 mm	M 5	8 mm	38,9
K-07 15 04 98	23,0	5 mm / 3 mm	G 1/8	14 mm	42,0
K-07 15 04 99	25,0	6 mm / 4 mm	G 1/8	14 mm	42,0
K-07 15 05 00	25,0	8 mm / 6 mm	G 1/8	14 mm	42,0
K-07 15 04 95	26,5	6 mm / 4 mm	G 1/4	17 mm	51,0
K-07 15 04 96	27,5	8 mm / 6 mm	G 1/4	17 mm	51,0
K-07 15 04 94	28,5	10 mm / 8 mm	G 1/4	17 mm	51,0