

# K-VORFILTER PC-BEHAEL SCHUTZ MUTIFI

Pre-filters with polycarbonate bowl and bowl guard

**HANSA FLEX**

## 属性

入口压力	Max. 16 bar
介质温度	max. 60 °C
环境温度	Max. 60 °C
过滤精度	0,30 µm
效率	99.999 %
密封材料	NBR
过滤器滤芯	Paper-POM
壳体	Die-cast zinc
Drain valve	Semi-automatic
流量值测量	FV at P1 = 6 bar and $\Delta p = 0.02$ bar



## 提示

\* = Dimensions with adapter plate!  
其它数据应客户要求提供。

## 描述

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

## 附加信息

on Art. K-07250721: Max. inlet pressure 300 bar. Other cylinder pressure regulators available on request.

## 货品

名称	螺纹	流量 (L/min)	A (mm)	B	C (mm)	D (mm)	DN
K- 07 25 10 70	G 1/4	160	47,8	152,1 mm	27,0	125,1	6
K- 07 25 10 73	G 1/2	500	68,8	180,8 mm (185,8 mm)*	72,0	147,3	15

## 备件

K-HALTERBAUSATZ MULTIFIX	Holder
K-KOPPELPAKET MEHR	Coupling packet
K-KOPPELPAKET SCHMA	Coupling packet
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-PC-BEHAELTER FILTER MULTIFIX	Polycarbonate tank filter
K-METALLBEHAELTER OELER MULTIFIX	Metal tank oiler