

K-VORFILTER M MANO

Pre-filters with differential pressure gauge

属性

| | |
|-----------|--|
| 入口压力 | Min. 4 bar, Max. 16 bar |
| 压差压力计显示范围 | 0 - 2 bar |
| 壳体,过滤器容器 | Aluminium |
| 环境温度 | +5 °C to +60 °C |
| 过滤精度 | 2,00 µm |
| 颗粒分离 | 2 µm |
| 效率 | 99.99 % |
| 过滤器滤芯 | Polyethylene (with 45% cavity) |
| 流量值测量 | At P1 = 6 bar and pressure drop $\Delta p = 0.5\%$ |



提示

其它数据应客户要求提供。

描述

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

货品

| 名称 | 螺纹 | 流量 (L/min) | A (mm) | B1 (mm) | B2 (mm) | C (mm) | D (mm) |
|----------------|---------|---------------|-----------|------------|------------|-----------|-----------|
| K- 07 25 12 86 | G 1/4 | 1000 | 82,5 | 407,0 | 335,0 | 57,0 | 353,0 |
| K- 07 25 12 87 | G 3/8 | 1000 | 82,5 | 407,0 | 335,0 | 57,0 | 353,0 |
| K- 07 25 12 88 | G 1/2 | 1000 | 82,5 | 407,0 | 335,0 | 57,0 | 353,0 |
| K- 07 25 12 89 | G 3/4 | 2000 | 82,5 | 477,0 | 405,0 | 57,0 | 493,0 |
| K- 07 25 12 90 | G 1 | 3000 | 118,0 | 492,0 | 420,0 | 72,0 | 458,0 |
| K- 07 25 12 91 | G 1 1/4 | 5300 | 118,0 | 592,0 | 520,0 | 72,0 | 658,0 |
| K- 07 25 12 92 | G 1 1/2 | 8300 | 118,0 | 692,0 | 620,0 | 72,0 | 858,0 |
| K- 07 25 12 93 | G 2 | 13000 | 118,0 | 882,0 | 810,0 | 72,0 | 1238,0 |

备件

| | |
|----------------------------|-----------------------------|
| K-FILTERELEMENT SONDER | Filter element |
| K-VERBINDUNGSELEMENTE SOND | Connecting sets |
| K-HALTERBAUSATZ | Holder |
| K-DIFFERENZDRUCKMANOMETER | Differential pressure gauge |
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |