

K-FI AK KOH METALLBEHAE MULTIFIX MI

Activated carbon filters with metal bowl

HANSA FLEX

属性

| | |
|-------------|---|
| 入口压力 | Max. 16 bar |
| 介质温度 | max. 60 °C |
| 环境温度 | Max. 60 °C |
| 密封材料 | NBR |
| 过滤器滤芯 | Activated carbon-POM |
| 壳体 | Die-cast zinc |
| Drain valve | Semi-automatic |
| 剩余油含量 | 0.005 mg/m ³ |
| 流量值测量 | FA at P1 = 6 bar and pressure drop $\Delta p = 0.2$ bar |



提示

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar.
其它数据应客户要求提供。

描述

Micro-filters for compliance with strict compressed air purity requirements. Suitable for all applications where standard filters do not afford the desired efficiency.

货品

| 名称 | 螺纹 | 流量 (L/min) | A (mm) | B | C (mm) | D (mm) | DN | 结构尺寸 |
|----------------|-------|---------------|-----------|---------|-----------|-----------|----|------|
| K- 07 25 10 46 | G 1/8 | 310 | 40,0 | 97,3 mm | 12,3 | 85,0 | 5 | 0 |

备件

| | |
|------------------------------|--|
| K-AUTOMAT ABLASSVENTIL | Automatic drain valve |
| K-KOPPELPAKET MEHR | Coupling packet |
| K-ERSATZBEHAELTER MULTI MINI | Spare tank »multifix-mini« & »standard-mini« |