


属性

工作压力	max. 70 bar (depending on temperature and nominal size)
校准值	G 1/4 to G 1: 20 °C: 70 bar, 60 °C: 65 bar, 100 °C: 45 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar G 1 1/4 to G 1 1/2: 20 °C: 70 bar, 60 °C: 55 bar, 100 °C: 35 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar G 2: 20 °C: 60 bar, 60 °C: 40 bar, 10
工作温度	200 °C at 0 bar
密封	15 % RPTFE (glass fibre reinforced PTFE)
手柄	Stainless steel 1.4301



提示

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

其它数据应客户要求提供。

订购指南

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

附加信息

G thread acc. DIN EN ISO 228-1

货品

名称	DN	螺纹	A (mm)	B (mm)	L (mm)	原料
K-07 30 15 36	5	G 1/4	69,0	34,0	39,0	Stainless steel 1.4401/1.4408
K-07 30 15 37	7	G 3/8	83,0	38,0	44,0	Stainless steel 1.4401/1.4408
K-07 30 15 38	10	G 1/2	96,0	41,0	59,0	Stainless steel 1.4401/1.4408
K-07 30 15 39	13	G 3/4	96,0	45,0	60,0	Stainless steel 1.4401/1.4408
K-07 30 29 80	16	G 1	116,0	52,0	72,0	Stainless steel 1.4401/1.4408
K-07 30 29 81	20	G 1 1/4	116,0	57,0	77,0	Stainless steel 1.4401/1.4408
K-07 30 29 82	25	G 1 1/2	158,0	62,0	84,0	Stainless steel 1.4401/1.4408
K-07 30 29 83	32	G 2	158,0	68,0	100,0	Stainless steel 1.4401/1.4408