

K-L-STECK VB 2

Union elbows

HANSA FLEX

属性

| | |
|------|------------------|
| 工作压力 | Max. 16 bar |
| 工作温度 | -20 °C to +80 °C |
| 原料 | 黄铜镀镍 |
| 紧压环 | Hostaform |
| 张紧环 | Stainless steel |



提示

其它数据应客户要求提供。

描述

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

货品

| 名称 | 用于软管外径-Ø | L1 (mm) | L2 (mm) |
|----------------|----------|------------|------------|
| K- 07 40 25 34 | 3 mm | 10,4 | 10,4 |
| K- 07 40 25 35 | 4 mm | 16,7 | 16,7 |
| K- 07 40 25 36 | 5 mm | 19,2 | 19,2 |
| K- 07 40 25 37 | 6 mm | 19,0 | 19,0 |
| K- 07 40 25 38 | 8 mm | 21,3 | 21,3 |
| K- 07 40 25 39 | 10 mm | 23,3 | 23,3 |
| K- 07 40 25 40 | 12 mm | 26,0 | 26,0 |
| K- 07 40 25 41 | 14 mm | 29,3 | 29,3 |