

# K-SPIR SCHL KUPPL SET SVKM

Spiral hose and coupling kits, with quick disconnect couplings DN 7.6

**HANSA** **FLEX**

## 属性

|      |                  |
|------|------------------|
| 工作压力 | 10 bar           |
| 介质温度 | -20 °C to +60 °C |



## 提示

其它数据应客户要求提供。

## 描述

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## 货品

| 名称             | 软管尺寸           | 螺旋管直径 Ø<br>(mm) | 工作长度<br>(m) |
|----------------|----------------|-----------------|-------------|
| K- 07 10 07 59 | 10 mm x 6,5 mm | 52              | 4,0         |
| K- 07 10 07 60 | 10 mm x 6,5 mm | 52              | 6,0         |
| K- 07 10 07 61 | 10 mm x 6,5 mm | 52              | 8,0         |
| K- 07 10 07 62 | 12 mm x 8 mm   | 65              | 4,0         |
| K- 07 10 07 63 | 12 mm x 8 mm   | 65              | 6,0         |
| K- 07 10 07 64 | 12 mm x 8 mm   | 65              | 8,0         |