

K-S-BKR M ENTL ABSCHL

Safety ball valves lockable, with relief port

HANSA FLEX

属性

| | |
|------|------------------------------|
| 工作压力 | 最大 10 巴 |
| 工作温度 | -20 °C to max. +100 °C |
| 排气孔 | M 5 |
| 螺纹描述 | Rp thread acc. to ISO 7-1 |
| 手柄 | Stainless steel - PVC coated |
| 球密封 | PTFE / NBR |
| 主轴密封 | PTFE |
| 原料 | 不锈钢 |



提示

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
其它数据应客户要求提供。

描述

2/2-way stainless steel safety ball valves. Specially designed for pneumatic applications. The ball valve can be locked manually and has a relief port.

附加信息

The price does not include a padlock. Please order separately.

货品

| 名称 | DN | 螺纹 | A (mm) | B (mm) | L (mm) |
|----------------|----|----------|-----------|-----------|-----------|
| K- 07 30 15 16 | 8 | Rp 1/4 | 100,0 | 50,0 | 55,0 |
| K- 07 30 15 17 | 10 | Rp 3/8 | 100,0 | 50,0 | 55,0 |
| K- 07 30 15 18 | 15 | Rp 1/2 | 130,0 | 60,0 | 65,0 |
| K- 07 30 15 19 | 20 | Rp 3/4 | 130,0 | 64,0 | 74,6 |
| K- 07 30 15 20 | 25 | Rp 1 | 165,0 | 71,0 | 88,0 |
| K- 07 30 15 21 | 32 | Rp 1 1/4 | 165,0 | 78,0 | 102,0 |
| K- 07 30 15 22 | 40 | Rp 1 1/2 | 190,0 | 86,0 | 110,0 |
| K- 07 30 15 23 | 50 | Rp 2 | 190,0 | 95,0 | 125,0 |

附件

K-VORHAENGESCHLOSS Padlock