

K-LP ALU O DUESE

Blow guns die-cast aluminium nickel-plated, without nozzle, Safety

HANSA FLEX

属性

| | |
|--------|------------------|
| 工作压力 | 最大 10 巴 |
| 工作温度 | -10 °C to +50 °C |
| 喷嘴和延长件 | Thread M12x1.25 |



提示

其它数据应客户要求提供。

描述

Standard type without nozzle! In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

货品

| 名称 | 接口 | 接口螺纹 |
|----------------|--|-------|
| K- 07 10 00 07 | Stem, I.D. 6 | G 1/4 |
| K- 07 10 00 10 | Stem, I.D. 9 | G 1/4 |
| K- 07 10 00 14 | Stem, I.D. 13 | G 1/4 |
| K- 07 10 00 18 | connection nipples for coupling NW 7,2 | G 1/4 |

附件

| | |
|------------------------------|--|
| K-ZUBEH LP ALU | Accessories for standard blow guns (series 22) |
| K-FEINSTRAHL DUE LAERMARME M | Low-noise fine-spray nozzles, M12x1.25 connection |
| K-RUNDDUESE LAERMARME M | Low-noise round nozzles, M12x1.25 connection |
| K-FLACHDUESE LAERMARME M | Low-noise flat nozzles, M12x1.25 connection |
| K-STANDARD DUESE | Standard nozzle (short version) with Ø 1.5 mm bore |
| K-DAEMPFER DUESE | Silencer nozzle, M12x1.25 connection |
| K-DUESE MIT SCHUTZSCHILD | Nozzle with chip shield, M12x1.25 connection |
| K-VERL DUESE | Extension nozzles |
| K-DRUCKREGULIER DUESE | Regulating nozzle, M12x1,25, Safety |