# K-RUNDDUESE LAERMARME

Low-noise round nozzles



## 提示

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

## 描述

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

## 货品

| 名称 | 螺纹 | 长度 (mm) | 喷嘴外径 Ø (mm) | 原料 | 示意图 |
|---|---|---|---|---|---|
| **K- 07 10 09 56** | G 3/8 male | 55,0 | 11 | Nickel-plated brass | 3 |
| **K- 07 10 09 57** | G 3/8 male | 50,0 | 10 | 铝 | 4 |
| **K- 07 10 09 58** | G 1/4 male | 41,0 | 13 | 铝 | 5 |
| **K- 07 10 09 59** | G 1/4 male | 46,0 | 17 | Die cast zinc | 6 |
| **K- 07 10 11 14** | G 1/4 male | 40,0 | 17 | Plastic (POM) | 7 |
| **K- 07 10 11 15** | G 1/4 male | 35,0 | 11 | 铝 | 8 |
| **K- 07 10 11 16** | G 1/4 male | 47,0 | 19 | Die cast zinc | 9 |
| **K- 07 10 11 17** | G 1/4 male | 55,0 | 19 | Plastic (ABS) | 10 |

*尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。*