K-SCHALLDAE SINTERBR SK

Silencers, sintered bronze, with hexagon nut

HANSA/FLEX

属	性

周任	
工作压力	0 - 8 bar
工作温度	-10 °C to +250 °C
6 巴噪音等级	71 ~ 108 dB(A)



提示

其它数据应客户要求提供。

描述

For reducing the exhaust noise generated by pneumatic equipment.

螺纹	А	В	С	SW
	(mm)	(mm)	(mm)	
G 1/8	6,0	28,0	8,0	13 mm
G 1/4	8,0	34,0	12,0	17 mm
G 3/8	10,0	36,0	15,0	22 mm
G 1/2	12,0	44,0	19,0	27 mm
G 3/4	14,0	54,0	22,0	32 mm
G 1	16,0	66,0	28,0	41 mm
	G 1/8 G 1/4 G 3/8 G 1/2 G 3/4	(mm) G 1/8 6,0 G 1/4 8,0 G 3/8 10,0 G 1/2 12,0 G 3/4 14,0	(mm) (mm) G 1/8 6,0 28,0 G 1/4 8,0 34,0 G 3/8 10,0 36,0 G 1/2 12,0 44,0 G 3/4 14,0 54,0	(mm) (mm) (mm) G 1/8 6,0 28,0 8,0 G 1/4 8,0 34,0 12,0 G 3/8 10,0 36,0 15,0 G 1/2 12,0 44,0 19,0 G 3/4 14,0 54,0 22,0