


# K-TR AG MS NI

Male hose fittings, parallel male thread - nickel plated brass

**HANSA FLEX**

## 属性

|      |             |
|------|-------------|
| 工作温度 | Max. 150 °C |
| 压力   | Max. 60 bar |
| 原料   | 黄铜镀镍        |



## 提示

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. 其它数据应客户要求提供。

## 描述

Suitable for air, water, oil, steam, etc.

## 附加信息

Further types and dimensions on request.

## 货品

| 名称             | 螺纹    | 用于软管     | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|----------|------------|------------|-------|
| K- 07 40 49 72 | G 1/8 | LW 6 mm  | 36,0       | 7,0        | 14 mm |
| K- 07 40 49 73 | G 1/8 | LW 8 mm  | 36,0       | 7,0        | 14 mm |
| K- 07 40 49 74 | G 1/8 | LW 9 mm  | 36,0       | 7,0        | 14 mm |
| K- 07 40 49 15 | G 1/4 | LW 4 mm  | 36,0       | 9,0        | 17 mm |
| K- 07 40 49 18 | G 1/4 | LW 6 mm  | 39,0       | 9,0        | 17 mm |
| K- 07 40 49 19 | G 1/4 | LW 8 mm  | 39,0       | 9,0        | 17 mm |
| K- 07 40 49 23 | G 1/4 | LW 9 mm  | 39,0       | 9,0        | 17 mm |
| K- 07 40 49 24 | G 1/4 | LW 10 mm | 39,0       | 9,0        | 17 mm |
| K- 07 40 49 25 | G 1/4 | LW 13 mm | 42,0       | 9,0        | 17 mm |
| K- 07 40 49 28 | G 3/8 | LW 8 mm  | 39,0       | 9,0        | 19 mm |
| K- 07 40 49 32 | G 3/8 | LW 9 mm  | 39,0       | 9,0        | 19 mm |
| K- 07 40 49 33 | G 3/8 | LW 10 mm | 39,0       | 9,0        | 19 mm |
| K- 07 40 49 35 | G 3/8 | LW 13 mm | 42,0       | 9,0        | 19 mm |
| K- 07 40 49 38 | G 1/2 | LW 8 mm  | 42,0       | 11,0       | 24 mm |
| K- 07 40 49 41 | G 1/2 | LW 9 mm  | 42,0       | 11,0       | 24 mm |
| K- 07 40 49 42 | G 1/2 | LW 10 mm | 42,0       | 11,0       | 24 mm |
| K- 07 40 49 47 | G 1/2 | LW 13 mm | 45,0       | 11,0       | 24 mm |
| K- 07 40 49 48 | G 1/2 | LW 16 mm | 53,0       | 11,0       | 24 mm |
| K- 07 40 49 49 | G 1/2 | LW 19 mm | 53,0       | 11,0       | 24 mm |
| K- 07 40 49 50 | G 3/4 | LW 13 mm | 51,0       | 12,0       | 32 mm |
| K- 07 40 49 51 | G 3/4 | LW 16 mm | 51,0       | 12,0       | 32 mm |
| K- 07 40 49 53 | G 3/4 | LW 19 mm | 54,0       | 12,0       | 32 mm |
| K- 07 40 49 55 | G 3/4 | LW 25 mm | 54,0       | 12,0       | 32 mm |
| K- 07 40 49 60 | G 1   | LW 25 mm | 49,0       | 15,0       | 34 mm |
| K- 07 40 49 68 | G 1   | LW 32 mm | 55,0       | 13,0       | 38 mm |