

K-ENDLAGEN-RUECKME KUNST M

End position feedback - plastic microswitch

属性

| | |
|--------|------------------------------------|
| 线缆螺旋接头 | M 20 x 1.5 |
| 最小开关功率 | 1 mA at 4 V DC |
| 额定开关功率 | 1 mA to 5 A at 250 V AC |
| 开关功能 | Changeover, silver-plated contacts |
| 保护等级 | IP 67, acc. to DIN EN 60529 |
| 温度范围 | -20 °C to +70 °C |
| 壳体 | Polyamide blue or black |
| 螺钉 | Stainless steel 1.4301 |
| 轴 | Polyamide PA6, black |
| 外盖 | Polycarbonate, transparent |
| 安装桥件 | PA6 with 30 % glass fibre |
| 密封 | EPDM and NBR |
| 密封材料 | NBR |



提示

其它数据应客户要求提供。

描述

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

货品

| 名称 | 定义 |
|----------------|--|
| K- 07 30 29 05 | End position feedback, M 2 type with microswitch |