


K-DRV GEW V RAENDEL

Unidirectional flow control valves, incoming air restriction (»V«),
screw connection

HANSA FLEX

属性

工作压力	最大 10 巴
温度范围	0 °C to +70 °C
空心螺钉,摆臂,调节螺钉	Nickel-plated brass
内部部件	Brass with a bare metal surface
O 形圈凸缘密封件	NBR
密封(防丢失)	Polyamide (glass fibre-reinforced)



提示

其它数据应客户要求提供。

描述

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

货品

名称	接口	C (mm)	螺纹	SW	B (mm)
K-07 15 25 19	M 5 female thread	11,5	M 5	8 mm	38,9
K-07 15 05 17	G 1/8 female thread	16,0	G 1/8	14 mm	42,4
K-07 15 05 13	G 1/4 female thread	22,0	G 1/4	17 mm	51,0
K-07 15 25 20	G 3/8 female thread	26,0	G 3/8	20 mm	63,0