

K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,
CrNi steel type

HANSA FLEX

属性

类型	233.50
规格	Glycerine-filled bourdon-tube pressure gauge, CrNi steel type
应用	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
质量等级	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
介质温度	max. +100 °C
环境温度	-20 °C 至 +60 °C
壳体	CrNi steel
密封片	Laminated safety glass Ø 63 = Polycarbonate



提示

其它数据应客户要求提供。

描述

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

货品

名称	测量范围	Ø (mm)	接口
K- 07 20 11 93	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 11 95	-1 / +0.6 bar	63,0	G 1/4"
K- 07 20 11 97	-1 / +1.5 bar	63,0	G 1/4"
K- 07 20 11 99	-1 / +3.0 bar	63,0	G 1/4"
K- 07 20 12 01	-1 / +5.0 bar	63,0	G 1/4"
K- 07 20 12 03	-1 / +9.0 bar	63,0	G 1/4"
K- 07 20 12 05	-1 / +15.0 bar	63,0	G 1/4"
K- 07 20 12 08	0 - 1.0 bar	63,0	G 1/4"
K- 07 20 12 10	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 12 12	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 12 14	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 12 16	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 12 18	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 12 20	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 12 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 12 24	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 12 26	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 12 28	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 12 30	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 12 32	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 12 34	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 12 36	0 - 600.0 bar	63,0	G 1/4"
K- 07 20 11 92	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 12 09	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100,0	G 1/2"

K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,
CrNi steel type

HANSA FLEX

货品

名称	测量范围	Ø (mm)	接口
K- 07 20 12 23	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160,0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160,0	G 1/2"