

# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,  
CrNi steel type

**HANSA FLEX**

属性	
类型	233.50
规格	Glycerine-filled bourdon-tube pressure gauge, CrNi steel type
应用	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
质量等级	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
介质温度	max. +100 °C
环境温度	-20 °C 至 +60 °C
壳体	CrNi steel
密封片	Laminated safety glass Ø 63 = Polycarbonate



## 提示

其它数据应客户要求提供。

## 描述

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

## 货品

名称	测量范围	Ø (mm)	接口
K- 07 20 11 93	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 11 95	-1 / +0.6 bar	63,0	G 1/4"
K- 07 20 11 97	-1 / +1.5 bar	63,0	G 1/4"
K- 07 20 11 99	-1 / +3.0 bar	63,0	G 1/4"
K- 07 20 12 01	-1 / +5.0 bar	63,0	G 1/4"
K- 07 20 12 03	-1 / +9.0 bar	63,0	G 1/4"
K- 07 20 12 05	-1 / +15.0 bar	63,0	G 1/4"
K- 07 20 12 08	0 - 1.0 bar	63,0	G 1/4"
K- 07 20 12 10	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 12 12	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 12 14	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 12 16	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 12 18	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 12 20	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 12 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 12 24	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 12 26	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 12 28	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 12 30	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 12 32	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 12 34	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 12 36	0 - 600.0 bar	63,0	G 1/4"
K- 07 20 11 92	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 12 09	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100,0	G 1/2"



尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。

23.07.2024

HANSA-FLEX AG

www.hansa-flex.com

1

# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,  
CrNi steel type



## 货品

名称	测量范围	Ø (mm)	接口
K- 07 20 12 23	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160,0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160,0	G 1/2"