

K-KURZH ZYL DOPPELW IG ASQ

Short-stroke cylinders, double-acting, with magnet, non-cushioned, with female thread, »ACQ« Series

HANSA FLEX

属性

| | |
|------|---|
| 适用介质 | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| 工作压力 | 1 - 10 bar (double-acting); 2 - 10 bar (single-acting) |
| 温度范围 | -20 °C to +80 °C |
| 活塞杆 | Hardened steel, thick-chromed |
| 活塞 | Brass (12 to 16 mm); Aluminium (20 to 100 mm) |
| 密封材料 | NBR |
| 缸管 | Aluminium |



提示

其它数据应客户要求提供。

描述

Specially for use where space is in short supply. Version with magnetic piston. Short-stroke cylinder in two different versions: Series "ACQ", double-acting, Ø 12 – 100

附加信息

Important: The scope of supply does not include a connector. Please order separately.

Other piston-Ø and stroke versions available on request.

货品

| 名称 | 活塞直径 Ø | 行程 (mm) | 结构形式 | 活塞杆直径 Ø (mm) | 活塞杆内螺纹 |
|----------------|--------|---------|------|--------------|-----------|
| K- 07 15 12 15 | 12 mm | 5 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 16 | 12 mm | 10 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 17 | 12 mm | 20 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 18 | 12 mm | 25 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 19 | 12 mm | 30 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 20 | 12 mm | 35 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 21 | 12 mm | 40 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 22 | 12 mm | 45 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 23 | 12 mm | 50 | 1 | 6 | M 3 x 0.5 |
| K- 07 15 12 24 | 16 mm | 5 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 25 | 16 mm | 10 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 26 | 16 mm | 20 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 27 | 16 mm | 25 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 28 | 16 mm | 30 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 29 | 16 mm | 35 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 30 | 16 mm | 40 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 31 | 16 mm | 45 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 32 | 16 mm | 50 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 33 | 16 mm | 55 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 34 | 16 mm | 60 | 1 | 8 | M 4 x 0.7 |
| K- 07 15 12 35 | 20 mm | 5 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 36 | 20 mm | 10 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 37 | 20 mm | 20 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 38 | 20 mm | 25 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 39 | 20 mm | 30 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 40 | 20 mm | 35 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 41 | 20 mm | 40 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 42 | 20 mm | 45 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 43 | 20 mm | 50 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 44 | 20 mm | 55 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 45 | 20 mm | 60 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 46 | 20 mm | 70 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 47 | 20 mm | 75 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 48 | 20 mm | 80 | 2 | 10 | M 5 x 0.8 |
| K- 07 15 12 49 | 25 mm | 5 | 2 | 12 | M 6 x 1 |



尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。

20.04.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-KURZH ZYL DOPPELW IG ASQ

Short-stroke cylinders, double-acting, with magnet, non-cushioned, with female thread, »ACQ« Series

HANSA FLEX

货品

| 名称 | 活塞直径 Ø | 行程 (mm) | 结构形式 | 活塞杆直径 Ø (mm) | 活塞杆内螺纹 |
|---------------|--------|---------|------|--------------|------------|
| K-07 15 12 50 | 25 mm | 10 | 2 | 12 | M 6 x 1 |
| K-07 15 12 51 | 25 mm | 20 | 2 | 12 | M 6 x 1 |
| K-07 15 12 52 | 25 mm | 25 | 2 | 12 | M 6 x 1 |
| K-07 15 12 53 | 25 mm | 30 | 2 | 12 | M 6 x 1 |
| K-07 15 12 54 | 25 mm | 35 | 2 | 12 | M 6 x 1 |
| K-07 15 12 55 | 25 mm | 40 | 2 | 12 | M 6 x 1 |
| K-07 15 12 56 | 25 mm | 45 | 2 | 12 | M 6 x 1 |
| K-07 15 12 57 | 25 mm | 50 | 2 | 12 | M 6 x 1 |
| K-07 15 12 58 | 25 mm | 55 | 2 | 12 | M 6 x 1 |
| K-07 15 12 59 | 25 mm | 60 | 2 | 12 | M 6 x 1 |
| K-07 15 12 60 | 25 mm | 70 | 2 | 12 | M 6 x 1 |
| K-07 15 12 61 | 25 mm | 75 | 2 | 12 | M 6 x 1 |
| K-07 15 12 62 | 25 mm | 80 | 2 | 12 | M 6 x 1 |
| K-07 15 12 63 | 32 mm | 5 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 64 | 32 mm | 10 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 65 | 32 mm | 20 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 66 | 32 mm | 25 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 67 | 32 mm | 30 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 68 | 32 mm | 35 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 69 | 32 mm | 40 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 70 | 32 mm | 45 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 71 | 32 mm | 50 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 72 | 32 mm | 55 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 73 | 32 mm | 60 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 74 | 32 mm | 70 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 75 | 32 mm | 75 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 76 | 32 mm | 80 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 77 | 40 mm | 5 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 78 | 40 mm | 10 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 79 | 40 mm | 20 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 80 | 40 mm | 25 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 81 | 40 mm | 30 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 82 | 40 mm | 35 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 83 | 40 mm | 40 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 84 | 40 mm | 45 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 85 | 40 mm | 50 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 86 | 40 mm | 55 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 87 | 40 mm | 60 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 88 | 40 mm | 70 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 89 | 40 mm | 75 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 90 | 40 mm | 80 | 3 | 16 | M 8 x 1.25 |
| K-07 15 12 91 | 50 mm | 5 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 92 | 50 mm | 10 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 93 | 50 mm | 20 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 94 | 50 mm | 25 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 95 | 50 mm | 30 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 96 | 50 mm | 35 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 97 | 50 mm | 40 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 98 | 50 mm | 45 | 3 | 20 | M 10 x 1.5 |
| K-07 15 12 99 | 50 mm | 50 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 00 | 50 mm | 55 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 01 | 50 mm | 60 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 02 | 50 mm | 70 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 03 | 50 mm | 75 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 04 | 50 mm | 80 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 05 | 63 mm | 5 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 06 | 63 mm | 10 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 07 | 63 mm | 20 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 08 | 63 mm | 25 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 09 | 63 mm | 30 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 10 | 63 mm | 35 | 3 | 20 | M 10 x 1.5 |
| K-07 15 13 11 | 63 mm | 40 | 3 | 20 | M 10 x 1.5 |



尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。

20.04.2026

HANSA-FLEX AG

www.hansa-flex.com

K-KURZH ZYL DOPPELW IG ASQ

Short-stroke cylinders, double-acting, with magnet, non-cushioned, with female thread, »ACQ« Series



货品

| 名称 | 活塞直径 Ø | 行程 (mm) | 结构形式 | 活塞杆直径 Ø (mm) | 活塞杆内螺纹 |
|----------------|--------|---------|------|--------------|------------|
| K- 07 15 13 12 | 63 mm | 45 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 13 | 63 mm | 50 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 14 | 63 mm | 55 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 15 | 63 mm | 60 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 16 | 63 mm | 70 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 17 | 63 mm | 75 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 18 | 63 mm | 80 | 3 | 20 | M 10 x 1.5 |
| K- 07 15 13 19 | 80 mm | 5 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 20 | 80 mm | 10 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 21 | 80 mm | 20 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 22 | 80 mm | 25 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 23 | 80 mm | 30 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 24 | 80 mm | 35 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 25 | 80 mm | 40 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 26 | 80 mm | 45 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 27 | 80 mm | 50 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 28 | 80 mm | 55 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 29 | 80 mm | 60 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 30 | 80 mm | 70 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 31 | 80 mm | 75 | 3 | 25 | M 16 x 2 |
| K- 07 15 13 32 | 80 mm | 80 | 3 | 25 | M 16 x 2 |
| K- 07 15 12 01 | 100 mm | 5 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 02 | 100 mm | 10 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 03 | 100 mm | 20 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 04 | 100 mm | 25 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 05 | 100 mm | 30 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 06 | 100 mm | 35 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 07 | 100 mm | 40 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 08 | 100 mm | 45 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 09 | 100 mm | 50 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 10 | 100 mm | 55 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 11 | 100 mm | 60 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 12 | 100 mm | 70 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 13 | 100 mm | 75 | 3 | 32 | M 20 x 2.5 |
| K- 07 15 12 14 | 100 mm | 80 | 3 | 32 | M 20 x 2.5 |

附件

| | |
|--------------------------------|---|
| K-FUSSBEFESTIGUNG TYP LB 3 | Foot model, »LB« type |
| K-FLANSCHBEFESTIGUNG TYP FA2 | Flange model, »FA« type |
| K-SCHWENKGABELBEFESTIG CB 1 | Female hinge model, »CB« type |
| K-GABELKOEPE TYP Y SET 1 | Fork model, »Y« type (incl. threaded adapter) |
| K-GELENKAUGEN TYP UNIT SET 1 | Rod eye model, »UNIT« type (incl. threaded adapter) |
| K-SENSOREN CS1 KH MIT STECKER | Sensors »CS1« type, cable with M8 plug |
| K-SENSOREN CS1 KH OHNE STECKER | Sensors »CS1« type, cable without plug |