K-DRV ABLD GEW C SCHLITZ


Unidirectional flow control valves, outgoing air restriction (»C«), screw connection



属性			
工作压力	最大 10 巴		
温度范围	0 °C to +70 °C		
空心螺钉,摆臂,调节螺钉	Nickel-plated brass		
内部部件	Brass with a bare metal surface		
O 形圖凸缘密封件	NBR		
密封(防丢失)	Polyamide (glass fibre-reinforced)		



www.hansa-flex.com



提示

其它数据应客户要求提供。

描述

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

货品					
名称	接口	C (mm)	螺纹	SW	B (mm)
K- 07 15 05 40	M 5 female thread	11,5	M 5	8 mm	24,5
K- 07 15 05 45	G 1/8 female thread	16,0	G 1/8	14 mm	32,0
K- 07 15 05 41	G 1/4 female thread	22,0	G 1/4	17 mm	40,0
K- 07 15 25 24	G 3/8 female thread	26,0	G 3/8	20 mm	50,0
K- 07 15 25 23	G 1/2 female thread	32,0	G 1/2	26 mm	61,0