


K-LKM S NW7,4 SCHL TUE

Safety couplings DN 7.4, with hose stem

HANSA FLEX

属性

工作压力	Max. 12 bar, maximum static working pressure (non-pulsating)
插入套管和内接头工作压力	0 to 35 bar
空气流量	1.300 l/min (at 6 bar and $\Delta p = 0.5$ bar)
介质温度	-20 °C to +60 °C
壳体, 阀体	Nickel-plated brass
阀	Brass
解锁套管	Plastic
弹簧、涨圈、销钉、球体	Stainless steel
密封材料	NBR



提示

其它数据应客户要求提供。

描述

One-hand air relief couplings with double locking system. Connection: Similar to standard couplings, simply by pressing the plug into the coupling. Disconnection: The first locking mechanism is accessible when the sleeve is pushed back. The coupling valve closes. Air can then then be relieved from the plug side (hose). The second locking mechanism is released by actuating the sleeve again. The coupling can now be disconnected. This system meets the requirements of ISO 4414 and is BIA-compliant (BIA = industrial safety institute).

货品

名称	接口	长度 (mm)	SW (mm)
K- 07 35 03 04	Stem, I.D. 6	71,2	22
K- 07 35 03 05	Stem, I.D. 8	71,2	22
K- 07 35 03 06	Stem, I.D. 9	71,2	22
K- 07 35 03 07	Stem, I.D. 10	71,2	22
K- 07 35 03 08	Stem, I.D. 13	71,2	22

附加元件

K-NIPPEL KUPPL NW7 AG VZ	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, male
K-NIPPEL KUPPL NW7 IG VZ 2	Plugs for couplings DN 7.2 - DN 7.8, hardened, galvanised steel, female
K-TUE 7,2 7,8 ST VZ 1	Stems for couplings DN 7.2 - DN 7.8, hardened, galvanised steel,