

# K-BOEGEN L IG IG 90°

Long sweep bends 2, 90°, female/female

## 属性

|      |   |
|------|---|
| 表面   | Hot dip galvanised                            |
| 温度范围 | -20 °C to +300 °C (at 20 bar)                 |
| 接口螺纹 | acc. ISO 7-1                                  |
| 原料   | Black malleable iron B350-10, design symbol A |
| 许可   | DIN DVGW                                      |



## 描述

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

## 附加信息

Further types and dimensions on request.

## 货品

| 名称             | 螺纹       |
|----------------|----------|
| K- 07 40 36 30 | Rp 1/4   |
| K- 07 40 36 33 | Rp 3/8   |
| K- 07 40 36 29 | Rp 1/2   |
| K- 07 40 36 32 | Rp 3/4   |
| K- 07 40 36 26 | Rp 1     |
| K- 07 40 36 28 | Rp 1 1/4 |
| K- 07 40 36 27 | Rp 1 1/2 |
| K- 07 40 36 31 | Rp 2     |
| K- 07 40 51 19 | Rp 2 1/2 |
| K- 07 40 51 20 | Rp 3     |