

# K-WV 3/2 5/2 NAMUR LB

3/2 and 5/2-way spool valves with NAMUR style interface



| 属性   |                               |
|------|-------------------------------|
| 适用介质 | Air, neutral gases (filtered) |
| 工作压力 | 1.5 - 8 bar                   |
| 工作温度 | +5 °C to +50 °C               |
| 电接口  | Plug connector PG 9           |
| 壳体   | Aluminium                     |
| 密封材料 | NBR                           |



提示

其它数据应客户要求提供。

描述

Pilot-operated 3/2 and 5/2-way spool valves with threaded ports and a NAMUR style interface. Combines high-quality design with a low price. By adding the conversion plate supplied with each valve, the device can be adapted to a 3/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

| 货品             |              |        |          |    |               |
|----------------|--------------|--------|----------|----|---------------|
| 名称             | 电压           | Port 1 | 接口 3 + 5 | DN | 流量<br>(L/min) |
| K- 07 15 00 09 | 230 V, 50 Hz | G 1/4  | G 1/4    | 8  | 1370          |
| K- 07 15 00 10 | 24 V DC      | G 1/4  | G 1/4    | 8  | 1370          |
| K- 07 15 00 11 | 230 V, 50 Hz | G 3/8  | G 1/4    | 10 | 1650          |
| K- 07 15 00 12 | 24 V DC      | G 3/8  | G 1/4    | 10 | 1650          |