


K-L-AGR-K OR DRH VA

Male run tees, conical male thread acc. to ISO 7-1, stainless steel

HANSA**FLEX**

属性

压力范围	Max. 25 bar
推荐的软管	PTFE hose
温度范围	-40 °C to +200 °C (depending on the hose quality and diameter)
原料	不锈钢 1.4404
密封	Pure metal



提示

其它数据应客户要求提供。

描述

Supplied without seals. For use with corrosive media and at high temperatures. Screw fitting series made of stainless steel for all applications where compliance with strict tightness, pressure and temperature requirements is essential. The parts are manufactured without rubber seals, in other words they are ideal for very high temperatures or for use with corrosive liquids, e.g. in cases when FPM is no longer suitable.

货品

名称	螺纹	用于软管	L1 (mm)	L2 (mm)	SW1 (mm)	SW2 (mm)
K-07 40 30 51	R 1/8	6 mm / 4 mm	23,0	40,0	12	10
K-07 40 30 52	R 1/8	8 mm / 6 mm	23,0	40,0	14	10
K-07 40 30 49	R 1/4	6 mm / 4 mm	23,0	44,5	12	10
K-07 40 30 50	R 1/4	8 mm / 6 mm	23,0	44,5	14	10
K-07 40 30 48	R 1/4	10 mm / 8 mm	26,0	47,5	16	12