

K-WV 3/2 LB NAMUR

3/2-way spool valves with NAMUR style interface, NC

HANSA FLEX

属性

| | |
|----------|---|
| 适用介质 | Air, neutral gases, filtered |
| 工作压力 | 1.5 to 10 bar |
| 工作温度 | -20 °C to +70 °C |
| 电接口 | Plug connector PG 9 |
| 包含在供货范围内 | Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws |
| 功率消耗 | 3 W=/5 VA~ |
| 壳体 | Aluminium, anodised |
| 滑座 | Stainless steel |
| 密封材料 | NBR |



提示

其它数据应客户要求提供。

描述

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

货品

| 名称 | 电压 | 接口 | DN | 流量 (L/min) |
|----------------|--------------|-------|----|---------------|
| K- 07 15 00 03 | 230 V, 50 Hz | G 1/4 | 7 | 1250 |
| K- 07 15 00 04 | 24 V DC | G 1/4 | 7 | 1250 |