K-DROSSELPLATT NAMUR VENTIL

Flow regulators for NAMUR valves

属性

适用介质	Air, neutral gases, filtered
工作压力	0.5 to 10 bar
工作温度	-20 °C to +70 °C
包含在供货范围内	1 coding pin (not for K-07152240), 2 O-rings, 2 fixing screws
壳体	Aluminium, anodised
原料	密封:NBR
密封材料	NBR



提示

其它数据应客户要求提供。

描述

Block-form flow regulator as an intermediate plate between the control valve and actuator acc. to the G 1/4 NAMUR standard. 3/2-way flow regulators: Independent regulation of the forward and return strokes of a single-acting pneumatic actuator. 5/2-way flow regulators: Regulation of the forward and return strokes of a double-acting pneumatic actuator.

货品

名称	功能	操纵件	DN	流量 (L/min)
K- 07 15 22 39	3/2-way	Knurled Screw	5	650
K- 07 15 22 40	3/2-way	Screwdriver	5	650
K- 07 15 22 41	5/2-way	Knurled Screw	5	650
K- 07 15 22 42	5/2-way	Screwdriver	5	650

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。