
K-BKR ROT STAHLHEBEL IG AG

Ball valves with red steel lever, lighweight type, female/male thread



属性					
应用范围	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture				
工作压力	Max. 40 bar				
工作温度	-15 °C to +90 °C				
螺纹描述	G thread acc. DIN EN ISO 228-1				
売体	Nickel-plated brass				
柄	Steel, with plastic coating				
球体	Chrome-plated brass				
球密封	PTFE				
主轴密封	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket				





提示

其它数据应客户要求提供。

货品					
名称	DN	螺纹	A (mm)	B (mm)	L (mm)
K- 07 30 00 50	8	G 1/4	85,0	42,0	44,0
K- 07 30 00 54	10	G 3/8	85,0	42,0	51,0
K- 07 30 00 58	15	G 1/2	85,0	46,0	60,0
K- 07 30 00 62	20	G 3/4	105,0	53,0	70,0
K- 07 30 00 66	25	G 1	105,0	57,0	79,0
K- 07 30 00 70	32	G 1 1/4	130,0	70,0	91,0
K- 07 30 00 74	40	G 1 1/2	130,0	76,0	104,0
K- 07 30 00 78	50	G 2	165,0	92,0	122,0