
## K-BKR BLAU STAHLHEBEL IG AG

Ball valves with blue steel lever, lighweight type, female/male thread



属性	
应用范围	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
工作压力	Max. 40 bar
工作温度	-15 °C to +90 °C
螺纹描述	G thread acc. DIN EN ISO 228-1
売体	Nickel-plated brass
柄	Steel, with plastic coating
球体	Chrome-plated brass
球密封	PTFE
主轴密封	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket





## 提示

其它数据应客户要求提供。

货品						
名称	DN	螺纹	A (mm)	B (mm)	L (mm)	
K- 07 30 00 48	8	G 1/4	85,0	42,0	44,0	
K- 07 30 00 52	10	G 3/8	85,0	42,0	51,0	
K- 07 30 00 56	15	G 1/2	85,0	46,0	60,0	
K- 07 30 00 60	20	G 3/4	105,0	53,0	70,0	
K- 07 30 00 64	25	G 1	105,0	57,0	79,0	
K- 07 30 00 68	32	G 1 1/4	130,0	70,0	91,0	
K- 07 30 00 72	40	G 1 1/2	130,0	76,0	104,0	
K- 07 30 00 76	50	G 2	165,0	92,0	122,0	