

K-MANO STAND H

Pressure gauges, CrNi steel, standard type, connection on rear, central

HANSA FLEX

属性

类型	131.11
规格	Bourdon-tube pressure gauge, CrNi steel type
应用	For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction
质量等级	2.5
介质温度	max. +100 °C
环境温度	-40 °C to +60 °C
壳体	CrNi steel
密封片	Polycarbonate



提示

其它数据应客户要求提供。

描述

Standard model manufactured entirely from CrNi steel, economical and reliable.

货品

名称	测量范围	Ø (mm)	接口
K- 07 20 03 93	0 - 1.0 bar	40,0	G 1/4
K- 07 20 03 94	0 - 1.6 bar	40,0	G 1/4
K- 07 20 03 95	0 - 2.5 bar	40,0	G 1/4
K- 07 20 03 96	0 - 4.0 bar	40,0	G 1/4
K- 07 20 03 97	0 - 6.0 bar	40,0	G 1/4
K- 07 20 03 98	0 - 10.0 bar	40,0	G 1/4
K- 07 20 03 99	0 - 16.0 bar	40,0	G 1/4
K- 07 20 04 00	0 - 25.0 bar	40,0	G 1/4
K- 07 20 04 01	0 - 40.0 bar	40,0	G 1/4
K- 07 20 04 02	0 - 60.0 bar	40,0	G 1/4
K- 07 20 04 03	0 - 100.0 bar	40,0	G 1/4
K- 07 20 04 94	0 - 1.0 bar	50,0	G 1/4
K- 07 20 04 95	0 - 1.6 bar	50,0	G 1/4
K- 07 20 04 96	0 - 2.5 bar	50,0	G 1/4
K- 07 20 04 97	0 - 4.0 bar	50,0	G 1/4
K- 07 20 04 98	0 - 6.0 bar	50,0	G 1/4
K- 07 20 04 99	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 00	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 01	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 02	0 - 40.0 bar	50,0	G 1/4
K- 07 20 05 03	0 - 60.0 bar	50,0	G 1/4
K- 07 20 05 04	0 - 100.0 bar	50,0	G 1/4