
K-BKR LANG IG AG

Ball valves, long-threaded type, female/male thread



属性					
应用范围	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture				
工作压力	Max. 40 bar				
工作温度	-15 °C to +90 °C				
螺纹描述	Thread acc. to ISO 7-1				
売体	Nickel-plated brass				
柄	Aluminium, painted black				
球体	Chrome-plated brass				
球密封	PTFE				
主轴密封	NBR / EPDM				





提示

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211) 其它数据应客户要求提供。

订购指南

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

附加信息

The pressure values refer to a maximum operating temperature of 40 °C. Lower maximum pressure apply at higher temperatures. See data sheet.

货品						
名称	DN	螺纹	A (mm)	B (mm)	L (mm)	
K- 07 30 21 37	8	Rp/R 1/4	85,0	42,0	52,0	
K- 07 30 21 38	10	Rp/R 3/8	85,0	42,0	54,0	
K- 07 30 21 39	15	Rp/R 1/2	85,0	46,0	67,0	
K- 07 30 21 40	20	Rp/R 3/4	105,0	53,0	78,0	
K- 07 30 21 41	25	Rp/R 1	105,0	57,0	89,0	
K- 07 30 21 42	32	Rp/R 1 1/4	130,0	70,0	103,0	
K- 07 30 21 43	40	Rp/R 1 1/2	130,0	76,0	113,0	
K- 07 30 21 44	50	Rp/R 2	165,0	92,0	136,0	