

# K-LKM S NW7,8 AG

Safety couplings DN 7.8, male

**HANSA FLEX**

## 属性

工作压力	最大 20 巴
空气流量	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
介质温度	-20 °C to +100 °C
阀体接口	Nickel-plated brass
弹簧, 球体	Stainless-steel
滑动套管	Anodised aluminium
解锁套管	Hardened and nickel-plated steel
密封材料	NBR



## 提示

其它数据应客户要求提供。

## 描述

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

## 货品

名称	接口	长度 (mm)	SW (mm)
K- 07 35 08 82	R 1/4 male	80,0	19
K- 07 35 08 83	R 3/8 male	81,0	19
K- 07 35 08 84	R 1/2 male	87,0	22

## 附加元件

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass