K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)

HANSA-FLEX

属性

类型	A-10
电压	8 - 30 V
电接口	With right-angle connector acc. to DIN EN 175301-803 A
保护等级	IP 65 acc. to EN 60529
输出信号	4 to 20 mA, 2-wire
非线性	0.5% of span
介质温度	0 °C to +80 °C
环境温度	0 °C to +80 °C
测量材料触碰的零件	CrNi steel 1.4404
壳体	CrNi steel 1.4404



提示

其它数据应客户要求提供。

描述

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

附加信息

Further measuring ranges on request

Pressure converter with output signal 0 - 10 V, 0 - 5 V and others on request.

货品

名称	测量范围	螺纹
K- 07 20 10 46	0 - 1.0 bar	G 1/4
K- 07 20 10 47	0 - 1.6 bar	G 1/4
K- 07 20 10 48	0 - 2.5 bar	G 1/4
K- 07 20 10 49	0 - 4.0 bar	G 1/4
K- 07 20 10 50	0 - 6.0 bar	G 1/4
K- 07 20 10 51	0 - 10.0 bar	G 1/4
K- 07 20 10 52	0 - 16.0 bar	G 1/4
K- 07 20 10 53	0 - 25.0 bar	G 1/4
K- 07 20 10 54	0 - 40.0 bar	G 1/4
K- 07 20 10 55	0 - 60.0 bar	G 1/4
K- 07 20 10 56	0 - 100.0 bar	G 1/4
K- 07 20 10 57	0 - 160.0 bar	G 1/4
K- 07 20 10 58	0 - 250.0 bar	G 1/4
K- 07 20 10 59	0 - 400.0 bar	G 1/4
K- 07 20 10 60	0 - 600.0 bar	G 1/4

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。