

K-DMUF 1

Pressure transmitters (CrNi steel 1.4404)

HANSA FLEX

| | |
|-----------|--|
| 属性 | |
| 类型 | A-10 |
| 电压 | 8 - 30 V |
| 电接口 | With right-angle connector acc. to DIN EN 175301-803 A |
| 保护等级 | IP 65 acc. to EN 60529 |
| 输出信号 | 4 to 20 mA, 2-wire |
| 非线性 | 0.5% of span |
| 介质温度 | 0 °C to +80 °C |
| 环境温度 | 0 °C to +80 °C |
| 测量材料触碰的零件 | CrNi steel 1.4404 |
| 壳体 | CrNi steel 1.4404 |



提示

其它数据应客户要求提供。

描述

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

附加信息

Further measuring ranges on request

Pressure converter with output signal 0 - 10 V, 0 - 5 V and others on request.

货品

| 名称 | 测量范围 | 螺纹 |
|----------------|---------------|-------|
| K- 07 20 10 46 | 0 - 1.0 bar | G 1/4 |
| K- 07 20 10 47 | 0 - 1.6 bar | G 1/4 |
| K- 07 20 10 48 | 0 - 2.5 bar | G 1/4 |
| K- 07 20 10 49 | 0 - 4.0 bar | G 1/4 |
| K- 07 20 10 50 | 0 - 6.0 bar | G 1/4 |
| K- 07 20 10 51 | 0 - 10.0 bar | G 1/4 |
| K- 07 20 10 52 | 0 - 16.0 bar | G 1/4 |
| K- 07 20 10 53 | 0 - 25.0 bar | G 1/4 |
| K- 07 20 10 54 | 0 - 40.0 bar | G 1/4 |
| K- 07 20 10 55 | 0 - 60.0 bar | G 1/4 |
| K- 07 20 10 56 | 0 - 100.0 bar | G 1/4 |
| K- 07 20 10 57 | 0 - 160.0 bar | G 1/4 |
| K- 07 20 10 58 | 0 - 250.0 bar | G 1/4 |
| K- 07 20 10 59 | 0 - 400.0 bar | G 1/4 |
| K- 07 20 10 60 | 0 - 600.0 bar | G 1/4 |